



Never compromise on quality!



LEVELMASTER LATEX LIQUID

Acrylic Liquid For Use With LevelMaster Standard Levelling Compound



LEVELMASTER RANGE

Description:



A latex liquid designed to be mixed with Bond It STANDARD Floor Levelling Compound to give increased flexibility and wearing characteristics.

Uses

LEVELMASTER LATEX LIQUID should be used to improve "water-mix" levelling compounds especially when used on substrates subject to slight movement i.e. timber or metal decks. It can also allow levelling compounds to be used as final finish in lightly trafficked areas.

Mixing

The liquid should be placed in a mixing bucket. Slowly add the powder component to the liquid latex, stirring quickly and continually, until a smooth paste develops. Only mix enough to use within 20 minutes. A mechanical stirrer is recommended for mixing. For every 20Kg of Bond It LEVELMASTER FLOORING COMPOUND use 1 container of Bond It LEVELMASTER LATEX LIQUID.



Application

Porous surfaces should be primed prior to application of levelling compound (use Bond It SBR or PRIMER & FLEXIBLE ADMIX).

Ambient temperature should be between 5°C and 30°C. Do not use in direct sunlight in conservatories. At 25°C the floor should be able to take light traffic in 2-3 hours and floorcoverings can be laid after 24 hours.

Do not try to reconstitute the mix once it has begun to set by adding more latex.

Coverage

1 pack of Latex per 20Kg of powder. Please refer to LevelMaster data sheet for full application details.

Container Size

5L plastic bottles.

Colour

White liquid.

Shelf Life

24 months from date of manufacture, when stored in unopened bottles.

Storage Conditions

Protect liquid from frost and high temperatures. Store at temperatures between 5 and 30°C. Protect from frost, high temperatures and out of direct sunlight.

Disposal of Containers

Do not leave empty containers where residue could be harmful to children, animals or the environment. Remove any containers to a central disposal point in accordance with local regulations.

Health & Safety

Please refer to separate material safety data sheet for full handling, use and storage instructions. Keep out of reach of children. It is the users responsibility to determine suitability for use. If in doubt contact our Technical Department for advice.

Note: this information is for general guidance only, since site conditions and labour are beyond our control. It is recommended that users make their own tests to determine suitability.

Specification Summary

Flammability	Non-flammable
Appearance	White liquid
Viscosity mPas	200 - 600
pH	Approximately 6.5-9
Solubility in Water	Soluble

Product Details:

Colour:	Grey
Colour:	BDH111
Size:	5L
Barcode:	5060021361349



Part of the Bond It LevelMaster Range

The data presented in this leaflet are in accordance with the present state of our knowledge, but do not absolve the user from carefully checking all supplies immediately on receipt. We reserve the right to alter product constants within the scope of technical progress or new developments. The recommendations made in this leaflet should be checked by preliminary trials because of conditions during processing over which we have no control, especially where other companies raw materials are also being used. The recommendations do not absolve the user from the obligation of investigating the possibility of infringement of third parties rights and, if necessary clarifying the position. Recommendations for use do not constitute a warranty, either expressed or implied, of the fitness or suitability of the products for a particular purpose.



Certificate Number:
6152
ISO 9001; ISO 14001;
ISO 45001

BOND IT

Head Office: Unit G16 River Bank Way, Lowfields Business Park,
Elland, West Yorkshire HX5 9DN.
Telephone: +44 (0)1422 315300 Fax +44 (0)1422 315310
Email: salesuk@bonditgroup.com Website: www.bonditgroup.com



V4 11/05/16
Supercedes: V3 11/08/15