

# Remover CT

# Revision: 4/12/2020

# Page 1 from 1

#### **Technical data**

Basis	Mixture based on natural solvents
Consistency	Aerosol
Density**	Ca. 0,85 g/ml
Application temperature	$5 ^{\circ}\text{C} \rightarrow 30 ^{\circ}\text{C}$

\* These values may vary depending on environmental factors such as temperature, moisture, and type of substrates. \*\* This information relates to fully cured product.

#### **Product description**

Remover CT is a non-aggressive mixture, based on natural solvents, suitable for removing fresh adhesive residues and most types of cured contact adhesive. Ideal for removing grease, oils and other dirt residues.

#### **Properties**

- Excellent cleaning properties
- Good degreasing properties
- Multi-purpose use
- Safe in use.
- Non-corrosive
- Free of (aromatic) hydrocarbons

#### Applications

- Removes hard excess contact glue.
- Suitable for removing fresh glue residues, oils, grease and other dirt residues

#### Packaging

Colour: transparent Packaging: 500 ml

#### Shelf life

2 years in unopened packaging in a cool and dry storage place at temperatures between +5°C and +25°C.

#### Application method

Application method: Shake can well before use. Spray at a distance of appr. 20 cm of the object. Apply as required. Leave to rest for a few minutes. After applying rub the surface dry with a clean towel. Always rub in one direction. Test for adverse effects on the surface in advance.

# **Health- and Safety Recommendations**

Use only in well-ventilated areas. In case of contact with eyes, wash immediately with plenty of water. Ingestion : rinse off the mouth with running water avoiding ingesting the liquid. Get in touch with a doctor. Consult label and material safety data sheet for more information.

# Remarks

- Not suitable for polystyrene and PMMA.
- Greasy residue may remain, this can be removed with a degreaser.
- Remover CT is not suitable to prepare the substrates for bonding. It is not a primer.
- Remover CT can cause staining on porous surfaces.
- Due to the wide variety of possible plastics and paints and to avoid damage to the surface, a preliminary compatibility test is recommended.

# Liability

The content of this technical data sheet is the result of tests, monitoring and experience. It is general in nature and does not constitute any liability. It is the responsibility of the user to determine by his own tests whether the product is suitable for the application.

Remark: This technical data sheet replaces al previous versions. The directives contained in this documentation are the result of our experiments and of our experience and have been submitted in good faith. Because of the diversity of the materials and substrates and the great number of possible applications which are out of our control, we cannot accept any responsibility for the results obtained. Since the design, the quality of the substrate and processing conditions are beyond our control, no liability under this publication is accepted. In every case it is recommended to carry out preliminary experiments. Soudal reserves the right to modify products without prior notice.

Everdongenlaan 18 - 20 Fax: +32 (0)14-42.65.14